In2net Knowledgebase

Changing Linux Agent Configuration

Option Name	Default Value	Description
ConfDir	/usr/sbin/r1soft/conf	Configuration directory path.
LogDir		Directory where the Backup Agent saves its log files.
LogFileMaxBytes	33554432	Sets the maximum size in bytes of an Server log file before it is rolled over and a new log file is created.
LogFileMaxFiles	10	LogFilesMaxFiles sets the maximum number of log files the Backup Agent will create before it starts deleting older log files. The value of zero will allow an unlimited number of files.
BindTo	0.0.0.0	The Backup Agent will listen for requests on this IP. Default is 0.0.0.0, meaning the Backup Agent accepts connections on any IP address configured on your Linux server.
LocalPort	1167	TCP port the Backup Agent will listen on.

The Linux Backup Agent installer automatically sets default parameters for the configuration file located in:
/usr/sbin/r1soft/conf/agent-config
After making changes to this file you need to restart the Agent daemon. To restart the Backup agent, use the following command:
/etc/init.d/cdp-agent restart
Backup Agent Configuration Options

Run the following command to list all configuration options
cat /usr/sbin/r1soft/conf/agent_config
or
less /usr/sbin/r1soft/conf/agent_config

https://kb.in2net.net/questions/521/