

### Changing Linux Agent Configuration

Option Name	Default Value	Description
ConfDir	/usr/sbin/r1soft/conf	Configuration directory path.
LogDir		Directory where the Backup Agent saves its log files.
LogFileMaxBytes	33554432	Sets the maximum size in bytes of an Server log file before it is rolled over and a new log file is created. LogFilesMaxFiles sets the maximum number of log files the Backup Agent will create before it starts deleting older log files. The value of zero will allow an unlimited number of files.
LogFileMaxFiles	10	The Backup Agent will listen for requests on this IP. Default is 0.0.0.0, meaning the Backup Agent accepts connections on any IP address configured on your Linux server.
BindTo	0.0.0.0	TCP port the Backup Agent will listen on.
LocalPort	1167	

The Linux Backup Agent installer automatically sets default parameters for the configuration file located in:  
/usr/sbin/r1soft/conf/agent-config

After making changes to this file you need to restart the Agent daemon. To restart the Backup agent, use the following command:

```
/etc/init.d/cdp-agent restart
```

Backup Agent Configuration Options

Run the following command to list all configuration options

```
cat /usr/sbin/r1soft/conf/agent_config
```

or

```
less /usr/sbin/r1soft/conf/agent_config
```

<https://kb.in2net.net/questions/521/>